

LAYFLAT HOSE 高壓扁喉

Characteristic & Application 特點及應用

This hose is weather resistant, lightweight; flexible; strong; collapsible when not in use and have a good degree of rot and chemical resistance.

PVC 扁喉，具有耐酸、耐鹼、耐寒、耐霉爛、耐老化、搬運輕便的、可折疊，使用壽命長的特點。本產品廣泛應用於農田、魚塘、草原、園林、工業、礦山、建築、油田等行業的輸水之用。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 爆破壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
LH2-6	53	51	6	18	100	0.4
LH3-10	79.4	76	10	30	100	0.6
LH4-10	107	102	10	30	100	1.0
LH6-8	158.4	152	8	24	100	1.6
LH8-5	203.4	200	5	15	100	2.2

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍			Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
LH2-6								
LH3-10	T52-55	SL60	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
LH4-10	T74-79	SL94	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
LH6-8	T104-112	SL115	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
LH8-5	T149-161	SL675	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
LH8-5	T201-213	SL875	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

SPIRAL SMOOTH HOSE 平面骨喉

Characteristic & Application 特點及應用

The hose is light, transparent with cold and hot resistance. It has good bending radius with high working pressure. This hose is suitable for pumping water, slurry, sewage.





輕身、透明、彎曲半徑小、耐壓。此喉可用於配合抽水、污水及泥漿。











Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
SSH-2	60	51	8	28	30	0.89
SSH-3	86.4	76	6	21	30	1.49
SSH-4	113.4	102	6	21	30	2.38
SSH-6	166	152	5	17.5	20	4.75

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
SSH-2									
SSH-2	T56-59	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
SSH-3	T80-85	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
SSH-4	T104-112	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
SSH-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

SPIRAL CORRUGATED HOSE 凸骨骨喉

Characteristic & Application 特點及應用

The hose is light, transparent with cold and hot resistance. It has good bending radius with high working pressure. This hose is suitable for pumping water, slurry, sewage.

輕身、透明、彎曲半徑小、耐壓。此喉可用於配合抽水、污水及泥漿。











Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
CSH-6	166	152	4	14.5	20	4.51
CSH-8	218	203	3	10.5	20	7.25

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
CSH-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
CSH-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

SPIRAL HEAVY DUTY HOSE 高壓骨喉

Characteristic & Application 特點及應用

The hose is light, transparent with cold and hot resistance. It has good bending radius with high working pressure. This hose is suitable for pumping water, slurry, sewage.










輕身、透明、彎曲半徑小、耐壓。此喉可用於配合抽水、污水及泥漿。











Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
HSH-2	61	51	8	28	30	1.11
HSH-3	87.4	76	6	21	30	1.53
HSH-4	114.4	102	6	21	30	2.42
HSH-6	167	152	5	17.5	20	4.85
HSH-8	220	202	4	14	20	7.88

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
									
HSH-2	T60-63	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
HSH-3	T86-91	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
HSH-4	T113-121	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
HSH-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
HSH-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

AW300 RUBBER HOSE 橡膠氣喉

Characteristic & Application 特點及應用

Heavy duty air hose suited for transfer of air and water in mining and construction industries.

此橡膠氣喉適能輸送空氣和水，適用於採礦和建築等。

Materials 物料

Black SBR/EPDM rubber, wrapped surface, abrasion and weather resistant. Multiply of high strength polyester cord.

黑色 SBR/EPDM 橡膠，表層為聚酯纖維。




Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
AW300-3/4	27	19	20	60	60	0.62
AW300-1	37	25.4	20	60	60	0.93
AW300-1.5	50	38	20	60	60	1.35
AW300-2	66	51	20	60	60	2.28
AW300-3	94	76	20	60	60	3.89
AW300-4	121	102	20	60	60	5.54

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
									
AW300-2	T64-67	SL76	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
AW300-3	T92-97	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
AW300-4	T113-121	SL525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

WS150 RUBBER HOSE WITH HELIX WIRE 鋼線橡膠喉

Characteristic & Application 特點及應用

This suction hose is suitable for use in agriculture, construction and mining industries. It is applicable for water and light slurry transfer in both negative and positive pressure applications.

此橡膠喉適用於農業、建築和採礦業，能有效地輸送水及少量泥漿。

Materials 物料

Black SBR rubber, piles of high strength polyester cord incorporating a steel wire helix.

黑色 SBR/ EPDM 橡膠，聚酯纖維結合鋼絲。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
WS150-2	63	51	10	30	30/60	2.12
WS150-3	90	76	10	30	30/60	3.64
WS150-4	118	102	10	30	30/60	5.58
WS150-6	170	152	10	30	6/20	9.68
WS150-8	224	202	10	30	6	14.18

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
WS150-2									
WS150-2	T60-63	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
WS150-3	T86-91	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
WS150-4	T113-121	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
WS150-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
WS150-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

WS300 RUBBER HOSE WITH HELIX WIRE 鋼線橡膠喉

Characteristic & Application 特點及應用

This suction hose is suitable for use in agriculture, construction and mining industries. It is applicable for water and light slurry transfer in both negative and positive pressure applications.

此橡膠喉適用於農業、建築和採礦業，能有效地輸送水及少量泥漿。

Materials 物料

Black SBR rubber, piles of high strength polyester cord incorporating a steel wire helix.

黑色 SBR/EPDM 橡膠，聚酯纖維結合鋼絲。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
WS300-4	120	102	20	60	60	6.23
WS300-6	174	152	20	60	20	10.95
WS300-8	227	202	20	60	10	28.47

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
									
WS300-4	T113-121	SL525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
WS300-6	T162-174	SL675/769	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
WS300-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

CD70 CEMENT RUBBER HOSE 石屎喉

Characteristic & Application

This suction hose is suitable for transfer of cement and concrete water in mining and construction industries.

此橡膠喉能輸送水泥及石屎，適用於採礦和建築等。

Materials 物料

Black SBR/EPDM rubber, wrapped surface, abrasion and water resistant. Multiply of high strength polyester cord.

黑色 SBR/EPDM 橡膠，表層為聚酯纖維。





Specification 產品規格

Product Code 產品編號	O.D. 外徑	I.D. 內徑	Working Pressure 工作壓力	Bursting Pressure 工作壓力	Standard Length 標準長度	Weight 重量
	mm	mm	bar	bar	m	Kg/m
CD70-4	116	102	5	15	30/60	3.04
CD70-6	168	152	5	15	20	4.87
CD70-8	222	202	5	15	10	10.18

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
									
CD70-4	T113-121	SL525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
CD70-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
CD70-8	T214-226	SL875	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench