



Goro Pump Panels

L531 PUMP STARTER PANEL 水泵起動控制箱

Characteristic & Application 特點及應用

Direct-on-line (D.O.L) starting Panel

L531 pump starter panel can control and protect three-phase pump.

The special design makes it a very reliable and sensitive protection

against pump dry running without installation of sensor in the deep well.

直接起動控制箱

此 L531 起動控制箱可以控制和保護三相水泵的運行。L531 起動控制箱特別的設計增加其可信賴性，而其敏感的保護可以避免水泵因沒有安裝浮波而導致乾涸運行的情況出現。

Characteristic 特點

- Built in function switch
Applied for water supply by liquid level control or booster
Applied for drainage by liquid level control
內置功能切換
適用於由液位控制或加速器的供水
適用於由液位控制的抽水
- Auto/ Manual switch
自動/手動切換
- Starts and stops the pump in accordance with different liquid level or pressure setting
按照不同液位或壓力設定，啟動或停止水泵運行
- Push button calibration
按鈕式校準
- Automatically stop the pump in case of the water shortage,
protecting it from dry running without installing the float switch or liquid probe in the well
在缺水的情況下，自動停止水泵運行，避免水泵因沒有安裝浮波而出現乾涸運行
- Pump accumulative running time displaying
顯示水泵累計運行時間
- Pump last five fault record displaying
顯示水泵最後五個故障記錄
- LCD displays pump running information
LCD 顯示水泵運行信息
- Protect the pump running many faults
避免水泵運作出現錯誤
- Grade of protection IP54
保護等級 IP54 等級
- Visual & audio alarm for fault prompt
配有故障提示燈及聲音報警作錯誤提示



Specification 產品規格

Model 型號	Voltage 供電電壓	Power Range 功率	Ampere Range 安培
L531-4	3 phase/380V	0.75-4kW	0-12A
L531-11	3 phase/380V	5.5-11kW	12-25A
L531-15	3 phase/380V	15kW	25-32A

可配合以下水泵使用

			
FSM Submersible Pump FSM 手提式自動抽水機	KBZ Submersible Pump KBZ 抽水機	KBS Slurry Pump KBS 泥漿泵	C Sewage Pump C 系污水泵