

FSM SUBMERSIBLE PUMP 手提式自動抽水泵

Characteristic & Application 特點及應用

Semi Vortex impeller design minimizes the clogging situation that can maximum durability and maintain pump performance.

Built-in shaft mounted agitator prevents the “air lock” and reduce the clogging situation.

半渦流葉輪設計大大減少泵殼內出現堵塞的情況，提升水泵的耐用性。內置軸承式攪拌器能防止“氣塞”的情況出現。



Specification 產品規格										
Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓	Motor Power 摩打功率		Max. Head 最高程揚	Max. Capacity 最大流量		Solid Passage 可容固體	Weight 重量
	inch	mm	V	kW	HP	m	l/s	m³/min	mm	kg
FSM-2.4F	2	50	110/220	0.4	0.55	12.0	3.5	0.21	9	16
FSM-2.75F	2	50	110/220	0.75	1	18.0	5.0	0.30	9	17
FSM-3.75F	3	80	110/220	0.75	1	18.0	5.0	0.30	9	19

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十二頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 22.

Hose & Hose Accessories 對應喉管及喉碼								
Model 型號	Hose 喉管		Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat Hose 扁喉	Spiral Hose 骨喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
								
FSM-2.4F	2" Layflat Hose		T52-55	SL60	2" Bauer	2" Camlock	2" Storz	2" Connector
FSM-2.75F	2" Spiral Hose		T56-59	SL60				
FSM-3.75F	3" Layflat Hose		T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose		T80-85	SL94				

Camlock Coupling 快速接頭							
							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭				
				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

KBZ SUBMERSIBLE PUMP 抽水機

Characteristic & Application 特點及應用

The pump body and motor is made of rigid cast iron for long-lasting durability. Semi-open impeller made of high chrome alloy match with wear plate achieves superior durability. Effective motor cooling due to discharge cast as part of the motor housing space economy by a top outlet.


硬質鑄造的外殼和馬達使水泵更持久耐用，鑄鐵機身及高鉻合金鑄造的半開式葉輪也提升了耐用性。另外，獨特出水口設計，使其在空氣中運轉仍可以確保冷卻效果。



Specification 產品規格										
Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓 V	Motor Power 摩打功率		Max. Head 最高程揚 m	Max. Capacity 最大流量		Solid Passage 可容固體 mm	Weight 重量 kg
	inch	mm		kW	HP		l/s	m³/min		
KBZ21.5	2	50	380	1.5	2	22.0	7.5	0.45	8.5	40
KBZ31.5	3	80	380			14.5	11.2	0.67	8.5	40
KBZ22.2	2	50	380	2.2	3	26.0	9.2	0.55	8.5	43
KBZ32.2	3	80	380			19.0	15.3	0.92	8.5	43
KBZ23.7	2	50	380	3.7	5	34.0	9.2	0.55	8.5	68
KBZ33.7	3	80	380			29.0	15.3	0.92	8.5	68
KBZ43.7	4	100	380			18.5	25.0	1.50	8.5	68
KBZ35.5	3	80	380	5.5	7.5	34.0	20.8	1.25	8.5	84
KBZ45.5	4	100	380			23.0	29.2	1.75	8.5	84
KBZ47.5	4	100	380	7.5	10	40.0	23.3	1.40	11.5	116
KBZ67.5	6	150	380			31.0	34.7	2.08	19.5	119
KBZ411	4	100	380	11	15	48.5	23.3	1.40	11.5	148
KBZ611	6	150	380			32.0	40.8	2.45	19.5	150
KBZ415	4	100	380	15	20	56.0	23.3	1.40	11.5	158
KBZ615	6	150	380			40.0	43.3	2.60	19.5	160

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十二頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 22.

Hose & Hose Accessories 對應喉管及喉碼								
Model 型號	Hose 喉管		Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat Hose 扁喉	Spiral Hose 骨喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
								
KBZ21.5 KBZ22.5 KBZ23.7	2" Layflat Hose		T52-55	SL60	2" Bauer	2" Camlock	2" Storz	2" Connector
	2" Spiral Hose		T56-59	SL60				
KBZ31.5 KBZ32.2 KBZ33.7 KBZ35.5	3" Layflat Hose		T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose		T80-85	SL94				
KBZ44.7 KBZ45.5 KBZ47.5 KBZ411 KBZ415	4" Layflat Hose		T104-112	SL115	4" Bauer	4" Camlock	4" Storz	4" Connector
	4" Spiral Hose		T104-112	SL115 / 525				
KBZ67.5 KBZ611 KBZ615	6" Layflat Hose		T149-161	SL675	6" Bauer	6" Camlock	6" Storz	6" Connector
	6" Spiral Hose		T162-174	SL675				

KBS SLURRY PUMP 泥漿泵

Characteristic & Application 特點及應用

This pump designed for handling raw sewage, wastewater, and heavy-duty industrial applications, where the pump is subject to clogging from oversize material. A tungsten carbide alloy edge blazed on the impeller vane on the serrated suction cover. This mechanism cuts incoming fibrous material into pieces, permitting smooth passage of fibrous material.

沉水式重型鑄鐵攪拌型四極泥漿泵，高鉻鋼鑄鐵攪拌器有助於快速地吸入沈澱物。其他零部件如葉輪和吸入蓋均採用高鉻鋼鑄鐵鑄造達到超強的耐磨性。



Specification 產品規格

Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓	Motor Power 摩打功率		Max. Head 最高程揚	Max. Capacity 最大流量		Solid Passage 可容固體	Weight 重量
	inch	mm	V	kW	HP	m	l/s	m ³ /min	mm	kg
80KBS44	3	80	380	4	5.5	14.8	27.5	1.65	30	119
100KBS46	4	100	380	6	8	16.9	40.0	2.40	30	151
150KBS49	6	150	380	9	12	21.5	53.3	3.20	30	183
200KBS415	8	200	380	15	20	22.0	103.3	6.20	30	278

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十二頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 22.

Hose & Hose Accessories 對應喉管及喉碼

Model 型號	Hose 喉管			Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat 扁喉	Spiral 骨喉	WS150 Hose 鋼線橡膠喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
									
80KBS44	3" Layflat Hose			T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose			T80-85	SL94				
	3" WS150 Rubber Hose			T86-91	SL94				
100KBS46	4" Layflat Hose			T104-112	SL115	4" Bauer	4" Camlock	4" Storz	4" Connector
	4" Spiral Hose			T104-112	SL115/525				
	4" WS150 Rubber Hose			T113-121	SL115/525				
150KBS49	6" Layflat Hose			T149-161	SL675	6" Bauer	6" Camlock	6" Storz	6" Connector
	6" Spiral Hose			T162-174	SL675				
	6" WS150 Rubber Hose			T162-174	SL675				
200KBS415	8" Layflat Hose			T201-213	SL875	8" Bauer	8" Camlock	-	8" Connector
	8" Spiral Hose			T214-226	SL988				
	8" WS150 Rubber Hose			T214-226	SL988				

C SEWAGE PUMP 污水泵

Characteristic & Application 特點及應用

This pump designed for handling raw sewage and wastewater applications, where the pump is subject to clogging from oversize material. A tungsten carbide alloy edge blazed on the impeller vane on the serrated suction cover. This pump cuts incoming fibrous material into pieces, permitting smooth passage of fibrous material.

C 系列污水泵，為因固型污物尺寸過大，導致堵塞問題的污水和廢水處理工業設計。裝有切刃刀頭的葉輪和鋸齒狀吸入蓋，可以切割和排出吸入的纖維物。



Specification 產品規格

Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓	Motor Power 摩打功率		Max. Head 最高程揚	Max. Capacity 最大流量		Solid Passage 可容固體	Weight 重量
	inch	mm	V	kW	HP	m	l/s	m³/min	mm	kg
50C27.5	2	50	380	0.75	1.0	12	6.67	0.4	20	30
50C2.75F	2	50	220	0.75	1.0	12	6.67	0.4	20	31
50C21.1	2	50	380	1.1	1.5	15	7.50	0.45	20	31
50C21.1F	2	50	220	1.1	1.5	15	7.50	0.45	20	32
50C21.5	2	50	380	1.5	2.0	13	8.67	0.52	25	42.5
80C21.5	3	80	380	1.5	2.0	13	14.3	0.86	25	42.5
50C22.2	2	50	380	2.2	3.0	17	9.67	0.58	25	48
80C22.2	3	80	380	2.2	3.0	17	17.0	1.02	25	48
80C23.0	3	80	380	3.0	4.0	21	18.7	1.12	30	60
80C24.0	3	80	380	4.0	5.5	24	22.0	1.32	30	63
100C25.5	4	100	380	5.5	7.5	27	29.6	1.78	35	91
100C27.5	4	100	380	7.5	10	30	33.3	2.0	35	98

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十二頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 22.

Hose & Hose Accessories 對應喉管及喉碼

Model 型號	Hose 喉管			Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat 扁喉	Spiral 骨喉	WS150 Hose 鋼線橡膠喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
50C27.5 50C2.75F 50C21.1 50C21.1F 50C21.5 50C22.2	2" Layflat Hose			T52-55	SL60	3" Bauer	3" Camlock	3" Storz	3" Connector
	2" Spiral Hose			T56-59	SL60				
80C21.5 80C22.2 80C23.0 80C23.0	3" Layflat Hose			T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose			T80-85	SL94				
	3" WS150 Rubber Hose			T86-91	SL94				
100C25.5 100C27.5	4" Layflat Hose			T104-112	SL115	4" Bauer	4" Camlock	4" Storz	4" Connector
	4" Spiral Hose			T104-112	SL115/525				
	4" WS150 Rubber Hose			T113-121	SL115/525				

FSM SUBMERSIBLE PUMP 手提式自動抽水泵

Characteristic & Application 特點及應用

Semi Vortex impeller design minimizes the clogging situation that can maximum durability and maintain pump performance.

Built-in shaft mounted agitator prevents the “air lock” and reduce the clogging situation.

半渦流葉輪設計大大減少泵殼內出現堵塞的情況，提升水泵的耐用性。內置軸承式攪拌器能防止“氣塞”的情況出現。



Specification 產品規格										
Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓	Motor Power 摩打功率		Max. Head 最高程揚	Max. Capacity 最大流量		Solid Passage 可容固體	Weight 重量
	inch	mm	V	kW	HP	m	l/s	m³/min	mm	kg
FSM-2.4F	2	50	110/220	0.4	0.55	12.0	3.5	0.21	9	16
FSM-2.75F	2	50	110/220	0.75	1	18.0	5.0	0.30	9	17
FSM-3.75F	3	80	110/220	0.75	1	18.0	5.0	0.30	9	19

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 20.

Hose & Hose Accessories 對應喉管及喉碼								
Model 型號	Hose 喉管		Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat Hose 扁喉	Spiral Hose 骨喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
								
FSM-2.4F	2" Layflat Hose		T52-55	SL60	2" Bauer	2" Camlock	2" Storz	2" Connector
FSM-2.75F	2" Spiral Hose		T56-59	SL60				
FSM-3.75F	3" Layflat Hose		T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose		T80-85	SL94				

Camlock Coupling 快速接頭							
							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭				
				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

KBZ SUBMERSIBLE PUMP 抽水機

Characteristic & Application 特點及應用

The pump body and motor is made of rigid cast iron for long-lasting durability. Semi-open impeller made of high chrome alloy match with wear plate achieves superior durability. Effective motor cooling due to discharge cast as part of the motor housing space economy by a top outlet.


硬質鑄造的外殼和馬達使水泵更持久耐用，鑄鐵機身及高鉻合金鑄造的半開式葉輪也提升了耐用性。另外，獨特出水口設計，使其在空氣中運轉仍可以確保冷卻效果。



Specification 產品規格										
Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓 V	Motor Power 馬打功率		Max. Head 最高程揚 m	Max. Capacity 最大流量		Solid Passage 可容固體 mm	Weight 重量 kg
	inch	mm		kW	HP		l/s	m³/min		
KBZ21.5	2	50	380	1.5	2	22.0	7.5	0.45	8.5	40
KBZ31.5	3	80	380			14.5	11.2	0.67	8.5	40
KBZ22.2	2	50	380	2.2	3	26.0	9.2	0.55	8.5	43
KBZ32.2	3	80	380			19.0	15.3	0.92	8.5	43
KBZ23.7	2	50	380	3.7	5	34.0	9.2	0.55	8.5	68
KBZ33.7	3	80	380			29.0	15.3	0.92	8.5	68
KBZ43.7	4	100	380			18.5	25.0	1.50	8.5	68
KBZ35.5	3	80	380	5.5	7.5	34.0	20.8	1.25	8.5	84
KBZ45.5	4	100	380			23.0	29.2	1.75	8.5	84
KBZ47.5	4	100	380	7.5	10	40.0	23.3	1.40	11.5	116
KBZ67.5	6	150	380			31.0	34.7	2.08	19.5	119
KBZ411	4	100	380	11	15	48.5	23.3	1.40	11.5	148
KBZ611	6	150	380			32.0	40.8	2.45	19.5	150
KBZ415	4	100	380	15	20	56.0	23.3	1.40	11.5	158
KBZ615	6	150	380			40.0	43.3	2.60	19.5	160

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 20.

Hose & Hose Accessories 對應喉管及喉碼								
Model 型號	Hose 喉管		Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat Hose 扁喉	Spiral Hose 骨喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
								
KBZ21.5 KBZ22.5 KBZ23.7	2" Layflat Hose		T52-55	SL60	2" Bauer	2" Camlock	2" Storz	2" Connector
	2" Spiral Hose		T56-59	SL60				
KBZ31.5 KBZ32.2 KBZ33.7 KBZ35.5	3" Layflat Hose		T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose		T80-85	SL94				
KBZ44.7 KBZ45.5 KBZ47.5 KBZ411 KBZ415	4" Layflat Hose		T104-112	SL115	4" Bauer	4" Camlock	4" Storz	4" Connector
	4" Spiral Hose		T104-112	SL115 / 525				
KBZ67.5 KBZ611 KBZ615	6" Layflat Hose		T149-161	SL675	6" Bauer	6" Camlock	6" Storz	6" Connector
	6" Spiral Hose		T162-174	SL675				

KBS SLURRY PUMP 泥漿泵

Characteristic & Application 特點及應用

This pump designed for handling raw sewage, wastewater, and heavy-duty industrial applications, where the pump is subject to clogging from oversize material. A tungsten carbide alloy edge blazed on the impeller vane on the serrated suction cover. This mechanism cuts incoming fibrous material into pieces, permitting smooth passage of fibrous material.

沉水式重型鑄鐵攪拌型四極泥漿泵，高鉻鋼鑄鐵攪拌器有助於快速地吸入沈澱物。其他零件如葉輪和吸入蓋均採用高鉻鋼鑄鐵鑄造達到超強的耐磨性。



Specification 產品規格

Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓	Motor Power 摩打功率		Max. Head 最高程揚	Max. Capacity 最大流量		Solid Passage 可容固體	Weight 重量
	inch	mm	V	kW	HP	m	l/s	m ³ /min	mm	kg
80KBS44	3	80	380	4	5.5	14.8	27.5	1.65	30	119
100KBS46	4	100	380	6	8	16.9	40.0	2.40	30	151
150KBS49	6	150	380	9	12	21.5	53.3	3.20	30	183
200KBS415	8	200	380	15	20	22.0	103.3	6.20	30	278

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 20.

Hose & Hose Accessories 對應喉管及喉碼

Model 型號	Hose 喉管			Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat 扁喉	Spiral 骨喉	WS150 Hose 鋼線橡膠喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
									
80KBS44	3" Layflat Hose			T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose			T80-85	SL94				
	3" WS150 Rubber Hose			T86-91	SL94				
100KBS46	4" Layflat Hose			T104-112	SL115	4" Bauer	4" Camlock	4" Storz	4" Connector
	4" Spiral Hose			T104-112	SL115/525				
	4" WS150 Rubber Hose			T113-121	SL115/525				
150KBS49	6" Layflat Hose			T149-161	SL675	6" Bauer	6" Camlock	6" Storz	6" Connector
	6" Spiral Hose			T162-174	SL675				
	6" WS150 Rubber Hose			T162-174	SL675				
200KBS415	8" Layflat Hose			T201-213	SL875	8" Bauer	8" Camlock	-	8" Connector
	8" Spiral Hose			T214-226	SL988				
	8" WS150 Rubber Hose			T214-226	SL988				

C SEWAGE PUMP 污水泵

Characteristic & Application 特點及應用

This pump designed for handling raw sewage and wastewater applications, where the pump is subject to clogging from oversize material. A tungsten carbide alloy edge blazed on the impeller vane on the serrated suction cover. This pump cuts incoming fibrous material into pieces, permitting smooth passage of fibrous material.

C 系列污水泵，為因固型污物尺寸過大，導致堵塞問題的污水和廢水處理工業設計。裝有切刃刀頭的葉輪和鋸齒狀吸入蓋，可以切割和排出吸入的纖維物。




Specification 產品規格

Model 型號 (50HZ)	Outlet 出水呎吋		Voltage 電壓	Motor Power 摩打功率		Max. Head 最高程揚	Max. Capacity 最大流量		Solid Passage 可容固體	Weight 重量
	inch	mm	V	kW	HP	m	l/s	m³/min	mm	kg
50C27.5	2	50	380	0.75	1.0	12	6.67	0.4	20	30
50C2.75F	2	50	220	0.75	1.0	12	6.67	0.4	20	31
50C21.1	2	50	380	1.1	1.5	15	7.50	0.45	20	31
50C21.1F	2	50	220	1.1	1.5	15	7.50	0.45	20	32
50C21.5	2	50	380	1.5	2.0	13	8.67	0.52	25	42.5
80C21.5	3	80	380	1.5	2.0	13	14.3	0.86	25	42.5
50C22.2	2	50	380	2.2	3.0	17	9.67	0.58	25	48
80C22.2	3	80	380	2.2	3.0	17	17.0	1.02	25	48
80C23.0	3	80	380	3.0	4.0	21	18.7	1.12	30	60
80C24.0	3	80	380	4.0	5.5	24	22.0	1.32	30	63
100C25.5	4	100	380	5.5	7.5	27	29.6	1.78	35	91
100C27.5	4	100	380	7.5	10	30	33.3	2.0	35	98

*可配合 L531 水泵起動控制箱使用，加強對水泵的保護。詳情請參閱第二十頁。

*To use with L531 pump starter panel to enhance pump protection. Please refer to page 20.

Hose & Hose Accessories 對應喉管及喉碼

Model 型號	Hose 喉管			Clamp 喉箍		Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯
	Layflat 扁喉	Spiral 骨喉	WS150 Hose 鋼線橡膠喉	T-Bolt 闊身喉碼	Omega 奧米茄碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭	
									
50C27.5 50C2.75F 50C21.1 50C21.1F 50C21.5 50C22.2	2" Layflat Hose			T52-55	SL60	3" Bauer	3" Camlock	3" Storz	3" Connector
	2" Spiral Hose			T56-59	SL60				
80C21.5 80C22.2 80C23.0 80C23.0	3" Layflat Hose			T74-79	SL94	3" Bauer	3" Camlock	3" Storz	3" Connector
	3" Spiral Hose			T80-85	SL94				
	3" WS150 Rubber Hose			T86-91	SL94				
100C25.5 100C27.5	4" Layflat Hose			T104-112	SL115	4" Bauer	4" Camlock	4" Storz	4" Connector
	4" Spiral Hose			T104-112	SL115/525				
	4" WS150 Rubber Hose			T113-121	SL115/525				

LAYFLAT HOSE 高壓扁喉

Characteristic & Application 特點及應用

This hose is weather resistant, lightweight; flexible; strong; collapsible when not in use and have a good degree of rot and chemical resistance.

PVC 扁喉，具有耐酸、耐鹼、耐寒、耐霉爛、耐老化、搬運輕便的、可折疊，使用壽命長的特點。本產品廣泛應用於農田、魚塘、草原、園林、工業、礦山、建築、油田等行業的輸水之用。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 爆破壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
LH2-6	53	51	6	18	100	0.4
LH3-10	79.4	76	10	30	100	0.6
LH4-10	107	102	10	30	100	1.0
LH6-8	158.4	152	8	24	100	1.6
LH8-5	203.4	200	5	15	100	2.2

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍			Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
								
LH2-6	T52-55	SL60	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
LH3-10	T74-79	SL94	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
LH4-10	T104-112	SL115	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
LH6-8	T149-161	SL675	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
LH8-5	T201-213	SL875	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

SPIRAL SMOOTH HOSE 平面骨喉

Characteristic & Application 特點及應用

The hose is light, transparent with cold and hot resistance. It has good bending radius with high working pressure. This hose is suitable for pumping water, slurry, sewage.

輕身、透明、彎曲半徑小、耐壓。此喉可用於配合抽水、污水及泥漿。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
SSH-2	60	51	8	28	30	0.89
SSH-3	86.4	76	6	21	30	1.49
SSH-4	113.4	102	6	21	30	2.38
SSH-6	166	152	5	17.5	20	4.75

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
SSH-2	T56-59	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
SSH-3	T80-85	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
SSH-4	T104-112	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
SSH-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

SPIRAL CORRUGATED HOSE 凸骨骨喉

Characteristic & Application 特點及應用

The hose is light, transparent with cold and hot resistance. It has good bending radius with high working pressure. This hose is suitable for pumping water, slurry, sewage.

輕身、透明、彎曲半徑小、耐壓。此喉可用於配合抽水、污水及泥漿。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
CSH-6	166	152	4	14.5	20	4.51
CSH-8	218	203	3	10.5	20	7.25

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
CSH-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
CSH-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

SPIRAL HEAVY DUTY HOSE 高壓骨喉

Characteristic & Application 特點及應用

The hose is light, transparent with cold and hot resistance. It has good bending radius with high working pressure. This hose is suitable for pumping water, slurry, sewage.

輕身、透明、彎曲半徑小、耐壓。此喉可用於配合抽水、污水及泥漿。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
HSB-2	61	51	8	28	30	1.11
HSB-3	87.4	76	6	21	30	1.53
HSB-4	114.4	102	6	21	30	2.42
HSB-6	167	152	5	17.5	20	4.85
HSB-8	220	202	4	14	20	7.88

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
HSB-2	T60-63	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
HSB-3	T86-91	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
HSB-4	T113-121	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
HSB-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
HSB-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

AW300 RUBBER HOSE 橡膠氣喉

Characteristic & Application 特點及應用

Heavy duty air hose suited for transfer of air and water in mining and construction industries.

此橡膠氣喉適能輸送空氣和水，適用於採礦和建築等。

Materials 物料

Black SBR/EPDM rubber, wrapped surface, abrasion and weather resistant. Multiply of high strength polyester cord.

黑色 SBR/ EPDM 橡膠，表層為聚酯纖維。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
AW300-3/4	27	19	20	60	60	0.62
AW300-1	37	25.4	20	60	60	0.93
AW300-1.5	50	38	20	60	60	1.35
AW300-2	66	51	20	60	60	2.28
AW300-3	94	76	20	60	60	3.89
AW300-4	121	102	20	60	60	5.54

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
AW300-2	T64-67	SL76	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
AW300-3	T92-97	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
AW300-4	T113-121	SL525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

WS150 RUBBER HOSE WITH HELIX WIRE 鋼線橡膠喉

Characteristic & Application 特點及應用

This suction hose is suitable for use in agriculture, construction and mining industries. It is applicable for water and light slurry transfer in both negative and positive pressure applications.

此橡膠喉適用於農業、建築和採礦業，能有效地輸送水及少量泥漿。

Materials 物料

Black SBR rubber, piles of high strength polyester cord incorporating a steel wire helix.

黑色 SBR/ EPDM 橡膠，聚酯纖維結合鋼絲。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
WS150-2	63	51	10	30	30/60	2.12
WS150-3	90	76	10	30	30/60	3.64
WS150-4	118	102	10	30	30/60	5.58
WS150-6	170	152	10	30	6/20	9.68
WS150-8	224	202	10	30	6/10	14.18

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
									
WS150-2	T60-63	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
WS150-3	T86-91	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
WS150-4	T113-121	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
WS150-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
WS150-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

WS300 RUBBER HOSE WITH HELIX WIRE 鋼線橡膠喉

Characteristic & Application 特點及應用

This suction hose is suitable for use in agriculture, construction and mining industries. It is applicable for water and light slurry transfer in both negative and positive pressure applications.

此橡膠喉適用於農業、建築和採礦業，能有效地輸送水及少量泥漿。

Materials 物料

Black SBR rubber, piles of high strength polyester cord incorporating a steel wire helix.

黑色 SBR/ EPDM 橡膠，聚酯纖維結合鋼絲。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
WS300-4	120	102	20	60	60	6.23
WS300-6	174	152	20	60	20	10.95
WS300-8	227	202	20	60	10	28.47

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
WS300-4	T113-121	SL525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
WS300-6	T162-174	SL675/769	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
WS300-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench



Goro Hoses

CD70 CEMENT RUBBER HOSE 石屎喉

Characteristic & Application

This suction hose is suitable for transfer of cement and concrete water in mining and construction industries.

此橡膠喉能輸送水泥及石屎，適用於採礦和建築等。

Materials 物料

Black SBR/EPDM rubber, wrapped surface, abrasion and water resistant. Multiply of high strength polyester cord.

黑色 SBR/ EPDM 橡膠，表層為聚酯纖維。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
CD70-4	116	102	5	15	30/60	3.04
CD70-6	168	152	5	15	20	4.87
CD70-8	222	202	5	15	10	10.18

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 閘身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
CD70-4	T113-121	SL525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
CD70-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
CD70-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

T-BOLT CLAMP 闊身喉碼

Characteristic & Application 特點及應用

The T-Bolt Clamp is constructed of plated steel. Uniform pressure creates a tight and reliable seal making them ideal for hoses.


闊身喉碼由鍍鋼製成，抗扭和耐壓能力良好，能有效地鎖緊喉管，是配合軟管一起使用的理想選擇。



Specification 產品規格

Model 型號	Application 可應用於
T52-55	2" GORO Layflat Hose
T56-59	2" GORO Smooth Spiral Hose
T60-63	2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose
T64-67	2" AW300 Rubber Hose
T74-79	3" GORO Layflat Hose
T80-85	3" GORO Smooth Spiral Hose
T86-91	3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose
T92-97	3" AW300 Rubber Hose
T104-112	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose
T113-121	4" GORO Heavy Duty Spiral Hose 4" AW300 Rubber Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" CD70 Cement Discharge Hose
T149-161	6" GORO Layflat Hose
T162-174	6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
T201-213	8" GORO Layflat Hose
T214-226	8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

			
Bauer Coupling 鮑爾接頭	Camlock Coupling 快速接頭	Hose Mender 鍍鋅接頭	Storz Coupling 德式接頭

Goro Clamps

OMEGA CLAMP 奧米茄碼

Characteristic & Application 特點及應用

The omega clamps feature a bolt on each side of the clamp. This allows the clamps to evenly distribute the pressure between two bolts instead of one. This makes it much safer, and more reliable with maintaining a seal.


奧米茄碼兩側具有螺栓，兩個螺栓能使壓力平均分佈，因此奧米茄碼可以承受較高的壓力。



Specification 產品規格

Model 型號	Application 可應用於
SL60	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose
SL76	2" AW300 Rubber Hose
SL94	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
SL115	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose
SL525	4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
SL675	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
SL769	6" WS300 Rubber Hose
SL875	8" GORO Layflat Hose
SL988	8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

			
Bauer Coupling 鮑爾接頭	Camlock Coupling 快速接頭	Hose Mender 鑲鋅接頭	Storz Coupling 德式接頭

Goro Clamps

SAFETY CLAMP 安全管夾

Characteristic & Application 特點及應用

'Safety' clamps are specifically designed for use with EN ISO 14420 (DIN 2817) hosetails fittings. The large rounded teeth inside the clamp halves securely grip the strong, tough hose cover, whilst the end of the clamp fits securely in to the groove on the hose tail.

This system is therefore double locked, also this clamps are light, so they are easy and safe to handle. Besides, safety clamps are rated to 16 Bar in all sizes.

安全管夾專門設計用於 EN ISO 14420 (DIN 2817) 套管接頭。管夾內部的大圓形齒可以牢固地夾緊喉管，堅固的軟管蓋，同時軟管可以牢固地夾於管夾末端凹槽中。因此，安全管夾能雙向鎖定喉管。此管夾輕巧，容易處理。另外，安全夾可承受壓力上限可高達 16 公斤。



Specification 產品規格

Model 型號	Application 可應用於
DIN 100x10	4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" AW300 Rubber Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" CD70 Cement Discharge Hose
DIN 150x13	6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
DIN 200x16	8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

		
DIN Camlock C+E DIN 快速接頭 C+E	Safety Clamp Insert with Victaulic Groove 溝槽式安全夾接頭	Victaulic Clamp 溝槽喉碼
需配合使用		

Goro Clamps **VICTAULIC CLAMP 溝槽喉碼**

Characteristic & Application 特點及應用

Victaulic clamp can use together with safety clamp and safety clamp insert with Victaulic groove and other Victaulic fittings and Victaulic valves.

溝槽喉碼可與安全管夾和溝槽式安全夾接頭配合使用，也可與其他溝槽管件和溝槽閥門配合使用。



Specification 產品規格

Model 型號	Application 可應用於
4 inch	4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" CD70 Cement Discharge Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose
6 inch	6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" CD70 Cement Discharge Hose 6" WS300 Rubber Hose
8 inch	8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

	
Safety Clamp Insert with Victaulic Groove 安全夾接頭	Safety Clamp 安全管夾
需配合使用	



Goro Clamps

BAUER COUPLING 鮑爾接頭

Characteristic & Application 特點及應用

Bauer couplings are designed primarily for use in irrigation, dewatering and other Industrial applications. This style of fitting is available galvanized steel in sizes ranging from 2" to 8". Bauer fittings can be coupled at offsets of up to 30 degrees depending on the diameter of the line. This benefit allows for easier installation and offers the end user greater flexibility when routing hoses and pipes.

鮑爾接頭是主要設計用於灌溉、排水和其他工業應用。此接頭常見呎吋是由 2" 到 8"，材質一般為鍍鋅鋼。鮑爾接頭接合時，最高可偏移 30 度，使安裝更方便，並且在軟管佈設時為使用戶提供更大的靈活性。



Specification 產品規格

Size 呎吋	Application 可應用於
2 inch	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose 2" AW300 Rubber Hose
3 inch	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
4 inch	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
6 inch	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
8 inch	8" GORO Layflat Hose 8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

	
T-Bolt Clamp 闊身喉碼	Omega Clamp 奧米茄碼

CAMLOCK COUPLING 快速接頭

Characteristic & Application 特點及應用

Camlocks Coupling is one of the most widely-used form of industrial connector in the field today. Most commonly, they are found in water suction & discharge applications.

快速接頭是當今最廣泛使用的工業接頭之一，最常見是用於吸水和排水。

							
Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Specification 產品規格

Size 呎吋	Application 可應用於
2 inch	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose 2" AW300 Rubber Hose
3 inch	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
4 inch	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
6 inch	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
8 inch	8" GORO Layflat Hose 8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

	
T-Bolt Clamp 闊身喉碼	Omega Clamp 奧米茄碼

Goro Clamps **STORZ COUPLING 德式接頭**

Characteristic & Application 特點及應用

The main benefit to using Storz couplings is speed of hose connection .

使用德式接頭主要好處是可以快速及簡單地地把喉管連接起來。

				
Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench

Specification 產品規格

Size 呎吋	Application 可應用於
2 inch	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose 2" AW300 Rubber Hose
3 inch	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
4 inch	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
6 inch	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose

可配合以下管件使用

	
T-Bolt Clamp 闊身喉碼	Omega Clamp 奧米茄碼



Goro Clamps

HOSE MENDER 鍍鋅接頭

Characteristic & Application 特點及應用

Hose mender works with all standard hose systems, and is designed for hose repairs, or to connect two hoses together.

鍍鋅接頭可與所有標準軟管配合使用，此產品能用於軟管維修或將兩個軟管連接在一起。



Specification 產品規格

Size 呎吋	Application 可應用於
2 inch	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose 2" AW300 Rubber Hose
3 inch	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
4 inch	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
6 inch	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
8 inch	8" GORO Layflat Hose 8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

	
T-Bolt Clamp 闊身喉碼	Omega Clamp 奧米茄碼

SAFETY CLAMP INSERT WITH VICTAULIC GROOVE 溝槽式安全夾接頭

Characteristic & Application 特點及應用

Safety Clamp Insert with Victaulic groove is specifically designed for use with EN ISO 14420 (DIN 2817) Safety Clamp and Victaulic clamp and is designed for connect two hoses.

溝槽式安全夾接頭與安全管夾和溝槽喉碼配合使用，此產品能將兩個軟管連接在一起。



Specification 產品規格

Model 型號	Application 可應用於
4 inch	4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" CD70 Cement Discharge Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose
6 inch	6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" CD70 Cement Discharge Hose 6" WS300 Rubber Hose
8 inch	8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用

	
Safety Clamp 安全夾	Safety Clamp 溝槽喉碼
需配合使用	



L531 PUMP STARTER PANEL 水泵起動控制箱

Characteristic & Application 特點及應用

Direct-on-line (D.O.L) starting Panel

L531 pump starter panel can control and protect three-phase pump.

The special design makes it a very reliable and sensitive protection against pump dry running without installation of sensor in the deep well.

直接起動控制箱

此 L531 起動控制箱可以控制和保護三相水泵的運行。L531 起動控制箱特別的設計增加其可信賴性，而其敏感的保護可以避免水泵因沒有安裝浮波而導致乾涸運行的情況出現。

Characteristic 特點

- Built in function switch
Applied for water supply by liquid level control or booster
Applied for drainage by liquid level control
內置功能切換
適用於由液位控制或加速器的供水
適用於由液位控制的抽水
- Auto/ Manual switch
自動/手動切換
- Starts and stops the pump in accordance with different liquid level or pressure setting
按照不同液位或壓力設定，啟動或停止水泵運行
- Push button calibration
按鈕式校準
- Automatically stop the pump in case of the water shortage, protecting it from dry running without installing the float switch or liquid probe in the well
在缺水的情況下，自動停止水泵運行，避免水泵因沒有安裝浮波而出現乾涸運行
- Pump accumulative running time displaying
顯示水泵累計運行時間
- Pump last five fault record displaying
顯示水泵最後五個故障記錄
- LCD displays pump running information
LCD 顯示水泵運行信息
- Protect the pump running many faults
避免水泵運作出現錯誤
- Grade of protection IP54
保護等級 IP54 等級
- Visual & audio alarm for fault prompt
配有故障提示燈及聲音報警作錯誤提示



Specification 產品規格

Model 型號	Voltage 供電電壓	Power Range 功率	Ampere Range 安培
L531-4	3 phase/380V	0.75-4kW	0-12A
L531-11	3 phase/380V	5.5-11kW	12-25A
L531-15	3 phase/380V	15kW	25-32A

可配合以下水泵使用

FSM Submersible Pump FSM 手提式自動抽水機	KBZ Submersible Pump KBZ 抽水機	KBS Slurry Pump KBS 泥漿泵	C Sewage Pump C 系污水泵