

Goro Hoses

WS150 RUBBER HOSE WITH HELIX WIRE 鋼線橡膠喉

Characteristic & Application 特點及應用

This suction hose is suitable for use in agriculture, construction and mining industries. It is applicable for water and light slurry transfer in both negative and positive pressure applications.

此橡膠喉適用於農業、建築和採礦業，能有效地輸送水及少量泥漿。

Materials 物料

Black SBR rubber, piles of high strength polyester cord incorporating a steel wire helix.

黑色 SBR/ EPDM 橡膠，聚酯纖維結合鋼絲。



Specification 產品規格

Product Code 產品編號	O.D. 外徑 mm	I.D. 內徑 mm	Working Pressure 工作壓力 bar	Bursting Pressure 工作壓力 bar	Standard Length 標準長度 m	Weight 重量 Kg/m
WS150-2	63	51	10	30	30/60	2.12
WS150-3	90	76	10	30	30/60	3.64
WS150-4	118	102	10	30	30/60	5.58
WS150-6	170	152	10	30	6/20	9.68
WS150-8	224	202	10	30	6	14.18

Hose Accessories 對應喉碼

Product Code 產品編號	Clamp 喉箍				Coupling 接頭			Galvanized Hose Connector 鍍鋅駁芯	Safety Clamp Insert 安全夾接頭
	T-Bolt 闊身喉碼	Omega 奧米茄碼	Safety 安全夾	Victaulic 消防碼	Bauer 鮑爾接頭	Camlock 快速接頭	Storz 德式接頭		
WS150-2									
WS150-2	T60-63	SL60	-	2"	2" Bauer	2" Camlock	2" Storz	2" Connector	2" Insert
WS150-3	T86-91	SL94	-	3"	3" Bauer	3" Camlock	3" Storz	3" Connector	3" Insert
WS150-4	T113-121	SL115/525	100x10	4"	4" Bauer	4" Camlock	4" Storz	4" Connector	4" Insert
WS150-6	T162-174	SL675	150x13	6"	6" Bauer	6" Camlock	6" Storz	6" Connector	6" Insert
WS150-8	T214-226	SL988	200x16	8"	8" Bauer	8" Camlock	-	8" Connector	8" Insert

Camlock Coupling 快速接頭

Adapter Type A	Coupler Type B	Coupler Type C	Adapter Type D	Adapter Type E	Adapter Type F	Coupler Type DC	Adapter Type DP

Storz Coupling 德式接頭

Male Thread	Female Thread	Hose Shank	Cap with Chain	Wrench